

Lieferprogramm 2023

Schleifmittel auf Unterlagen



Folie
FM, FS, FOS = hochreißfeste Kunststofffolie

GEWEBE



Art.-Nr.	Fertigungs- breite in mm	P 12	P 16	P 24	P 30	P 36	P 40	P 50	P 60	P 80	P 100	P 120	P 150	P 180	P 220	P 240	P 280	P 320	P 360	P 400	P 500	P 600	P 800	P 1000	P 1200	P 1500	P 2000	P 2500	ST3000	ST4000	ST5000	ST7000	Flexibilität 1 = steif 15 = flexibel	Über- zug	Produktfarbe der Kornseite	Anwen- dung				
Keramikkorn																																								
051 XP *	1480			•																															3	•	rotbraun	M		
	1650									•	•		•																						3	•	rotbraun	M		
051 XYP *	1650					•	•																												3	•	rotbraun	M		
052 J *	1650									•	•	•	•	•	•	•																		8	•	blau	M			
052 JFF *	1650									•		•	•	•																					10	•	blau	M		
052 XF *	1650									•	•	•	•	•	•		•																		7	•	blau	M		
062 XP *	1650					•	•	•	•	•	•	•	•																						3		lila	HM		
062 XPK *	1650					•	•	•	•	•	•	•	•																						3		lila	HM		
Zirkonkorund																																								
141 XP *	1650								•	•	•	•	•																							3		blau	M	
141 XYP *	1650			•		•	•																													3		blau	M	
144 XP *	1650					•	•				•	•	•																							4		blau	M	
151 XP *	1650									•	•	•	•	•	•																					3	•	blau	M	
151 XYP *	1650					•	•																													3	•	blau	M	
341 X *	1650			•		•	•		•	•	•	•	•																							6		blau	HM	
341 XK *	1650			•		•	•		•	•	•	•	•																							6		blau	HM	
341 XP *	1650			•		•	•	•	•	•	•	•	•																							4,5		blau	HM	
Korund																																								
500 NET	1400									•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								9		rotbraun	FHK	
531 J	1650								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								8		rotbraun	M	
531 JFF	1650								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•							9		rotbraun	M	
541 JF	1650								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								9		blau	M	
541 XF	1650					•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								7		rotbraun	M	
542 JFF	1650								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									10		rotbraun	HM
542 JFF5	1650											•	•		•																					10	•	weiß	H	
543 X	1650		•	•	•	•																														5		rotbraun	H	
543 XK	1650		•																																	5		rotbraun	H	
552 JFF	1650								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									10	•	blau	M
562 JFF	1650										•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									11		lila	M
641 PF	1650							•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									9		rotbraun	M
641 X	1650							•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									6		rotbraun	M
641 X, T01	1650							•	•	•	•	•	•																							5		rotbraun	H	
641 XP	1650								•	•	•	•	•	•	•	•																				3		rotbraun	M	
641 XYP	1650			•		•	•																														3		rotbraun	M
642 XF/N	1650			•		•		•	•	•	•	•	•																								7		rotbraun	HM
681 X	1650																	•		•																6		rotbraun	M	
732 X	1650							•	•	•	•	•	•																							6		rotbraun	HM	
Silicium-Carbid																																								
942 J	1650									•	•	•	•	•	•	•	•	•	•																	8		schwarz	KM	
942 JFF	1650										•								•																	9		schwarz	M	
942 JFF5	1650																			•		•	•	•												9	•	weiß	KM	
942 XP	1650							•	•	•	•	•	•	•	•																						3		schwarz	KMS
942 XYP	1650			•	•	•	•																														3		schwarz	KMS
942 XPS	1650								•																												3		schwarz	KMS
943 X	1650		•	•																																	5		schwarz	H
981 X	1650									•	•	•	•	•	•	•	•	•	•		•															6		schwarz	S	
981 XS	1650											•			•																						6		schwarz	S
Pearl-Grinding CP-Technologie																																								
A41 XP	1650									•	•		•	•	•	•	•	•	•		•		•	•												3		blau	M	
A44 X	1650											•																									3		blau	M
A81 XP **	1650						•		•	•	•	•																												

* = keine P-Körnungen | ** = nur für Nassschliff auf schweren Maschinen | *** = STARCKE-eigener Feinstkorn-Standard

STARCKE GmbH & Co. KG
Markt 10
D-49324 Melle
Telefon +49 (0)5422 966-0
Telefax +49 (0)5422 966-301
info@starcke.de
www.starcke.de